


**12, 16 and 19-Pin Field Wireable, Front Mount**

- For Use with Custom Wiring & Junction Boxes
- Convert Hard Wiring into Quick Disconnect
- IEC IP65 Protection



Housing Style	Female Part Number	Features	Pinout	
<p><b>CKF(S) ..</b></p>	<p><b>CKF 12-0</b> <b>CKFL 12-0</b></p>	<p>Nickel plated brass, accepts up to 12x18 AWG conductor, 125°C, 300 V, 8.0 A, field wireable 12-pin receptacle, for use with <i>minifast</i>®, <i>eurofast</i>® (single input per port) and <i>microfast</i>® junctions boxes</p>	<p><b>Female</b></p>	
	<p><b>CKF 16-0</b> <b>CKFL 16-0</b></p>	<p>Nickel plated brass, accepts up to 16x18 AWG conductor, 125°C, 150 V, 8.0 A, field wireable 16-pin receptacle, for use with <i>eurofast</i> (isolated power supply) junctions boxes</p>	<p><b>Female</b></p>	
	<p><b>CKF 19-0</b> <b>CKFL 19-0</b></p>	<p>Nickel plated brass, accepts up to 19x18 AWG conductor, 125°C, 150 V, 8.0 A, field wireable 19-pin receptacle, for use with <i>eurofast</i> (two signals per port) junctions boxes</p>	<p><b>Female</b></p>	
	<p><b>CKF(S)L</b></p>	<p><b>CSF 12-0</b> <b>CSFL 12-0</b></p>	<p>Nickel plated brass, accepts up to 12x18 AWG conductor, 125°C, 300 V, 8.0 A, field wireable 12-pin receptacle, for use with <i>minifast</i>®, <i>eurofast</i>® (single input per port) and <i>microfast</i>® junctions boxes</p>	<p><b>Male</b></p>
		<p><b>CSF 16-0</b> <b>CSFL 16-0</b></p>	<p>Nickel plated brass, accepts up to 16x18 AWG conductor, 125°C, 150 V, 8.0 A, field wireable 16-pin receptacle, for use with <i>eurofast</i> (isolated power supply) junctions boxes</p>	<p><b>Male</b></p>
		<p><b>CSF 19-0</b> <b>CSFL 19-0</b></p>	<p>Nickel plated brass, accepts up to 19x18 AWG conductor, 125°C, 150 V, 8.0 A, field wireable 19-pin receptacle, for use with <i>eurofast</i> (two signals per port) junctions boxes</p>	<p><b>Male</b></p>